

# castle

## COMPOSITES

### **Instructions**

### **Puzzle Gym Tiles**

#### **Instructions for processing rubber tiles for GYM/FITNESS purposes**

##### **Surface:**

Make sure you have a flat surface. If the subsurface does not consist of concrete, please contact us.

##### **Product features:**

Rubber granulate products can have a size tolerance/effect of no more than 2% and a thickness tolerance of no more than 5%. Rubber granulate products are made from recycled rubber, which contains Carbon Black which could come out as a black colouring agent

##### **Tools:**

Use the right tool like a straight strip or ruler, coarse teeth handsaw or jigsaw (low-speed engine), Stanley knife or a similar knife. Never use angle grinders, crosscut saws or saw tables

##### **Laying the product:**

Measure carefully (not too tight as tiles can expand due to moisture absorption and shrinking by weather influences)

Place the tiles on a concrete surface

\*\*\*\*\*

Keep the ruler or strip on the section you need

Moisten the cutting edge of the knife

Saw/cut the straight pieces using a handsaw, jigsaw or Stanley knife

Preferably use a jigsaw for cutting patterns

When processing artificial grass tiles please always note the arrows on the bottom of the tiles

##### **Maintenance:**

Vacuum, sweep

Scrubber or polishing/cleaning machine  
Hand cleaning products (hard brushes and soap)

Note: cleaning agents are allowed, provided corrosive agents are avoided  
Always wear/use the right protective gear when processing the products  
If you need more information about cleaning products, please contact us

Castle Composites Ltd  
Units 1-5 Nisbet Way  
Ravenstruther  
Lanark  
ML11 7SF

Call: 01555 870003  
Email: [sales@castlecomposites.co.uk](mailto:sales@castlecomposites.co.uk)

Version: 23-08-2016