



## dFlect Recycled Rubber Tiles

### Data Sheet

Material composition: binding agent and possibly a	Recycled granulate bound using a PU colouring agent.
Size:	500 x 500 mm / 1.000 x 1.000 mm
Thicknesses	25 30 40 45 50 65 100 mm.
Colours:	black, red, green, sand and grey. These colours are not colourfast and differences in colour may occur as this is a recycled product.
Density:	800 kg/m <sup>3</sup>
Fire resistance:	Efl to EN 13501
Smoke resistance:	S2
TÜV:	Dflect rubber tiles are TÜV certified. They meet the Attractions and Playground Apparatus Act EN1177
Size tolerance:	width 2% and thickness 5%
Colour:	The product is not colour fast and the colour may change due to influences of the weather and walking on the tiles
Carbon black: which exists in every rubber influences	Carbon black is a black colouring agent tile and which can come out due to of the weather.
Quicklime/cement veiling:	due to weather influences and quicklime/cement veiling of the surrounding objects the tiles and mats might develop a white

efflorescence.

Guarantee: 3 year guarantee for wear-resistance, with the exception of tiles that are used intensively. The guarantee does not apply to colour.

Recycling: Products are 100% recyclable.

Water permeability: 350 mm per hour EN 12616

Version: 19-03-2014