



---

## SAFETY DATA SHEET

### Rubber Acoustic / Protection Roll

#### PRODUCT AND COMPANY IDENTIFICATION

Product type: Rubber Roll  
Trade Name: "Accoustic / Protection Rubber Roll"  
Manufacturer: dFlect Rubber Tiles  
Units 1-5, Nisbet Way  
Ravenstruther  
Lanark, ML11 7SF  
Phone No.: 01555 870003  
Fax No.: 01555 870040

#### Packing Information

Rolled onto cardboard tubes.  
Stacked on wooden pallets with shrink wrap.

#### Product Information

**Composition:** Recycled Rubber Granulate bound with a cold cure PUR elastomer bonding agent.

**Thickness:** 5,6,8,10,12 & 15mm

**Density:** 730kg/m<sup>3</sup> (higher density available upon request)

**Fire Resistance:** EFL to EN 13501

**Long Term Thermal Stability:** -40 to +80 degrees centigrade

**Short Term Thermal Stability:** Up to 110 degrees centigrade

**Hardness:** Shore 55A as per EN13501-1+A1:2010

**Tensile Strength:** 0.46 N/mm<sup>2</sup> as per EN ISO 1798

**Compression Test at 10%:** 0.24 MPA

**Modulus of Elasticity:** 2.75 MPa

**Chemical Resistance:** Resistant to weak acids and lyes. Conditionally resistant to oils.

**Thermal Conductivity:** 0.14 W/m K as per DIN 52612